



ACX NON-METALLIC SHEATHED CABLE (TYPE NM)

- Composed of two PVC insulated solid or stranded conductors laid parallel to one another and banded by a PVC jacket.
- For fixed installations in both exposed and concealed works in dry location.
- Maximum circuit voltage is 600 volts and not to exceed for continuous operation of conductor temperature at 60°C

Reference Standard -- PNS 35-1:2004 / PNS 260 / PNS 1207

| NOMINAL SIZE mm | CONDUCTOR COMPOSITION | | NOM. OUTSIDE DIAMETER mm | INSULATION THICKNESS mm | NOM. JACKET THICKNESS mm | APPROX. OVERALL DIMENSION | | | TEST VOLTAGE A.C KV | MIN.INSULATION RESISTANCE @ 20°C MΩ / Km | STANDARD CUTTING LENGTH meters |
|-----------------------|--------------------------|--------|--------------------------------|-------------------------------|--------------------------------|---------------------------|-------|-------|------------------------------|---------------------------------------------------|-----------------------------------------|
| | pc | mm Ø | | | | 2C | 3C | MINOR | | | |
| 1.6 | 2 | x 1.60 | 1.60 | 0.80 | 0.80 | 9.58 | 14.36 | 4.80 | 5 | 50 | 75 |
| 2.0 | 2 | x 2.00 | 2.00 | 0.80 | 0.80 | 10.38 | 15.56 | 5.20 | 5 | 50 | 75 |
| 2.6 | 2 | x 2.60 | 2.60 | 0.80 | 0.80 | 11.58 | 17.36 | 5.80 | 5 | 50 | 75 |



Manufactured by:
AC HARRIS
CABLE CORPORATION
PHILIPPINES



#5 Pio del Pilar corner Magat Salamat St., Concepcion II, Marikina City, Philippines
Telephone Nos. (632) 941-2967 ; (632) 941-2968 ; (632) 941-2969 Fax No. (632) 997-8137 Globelines: (632) 955-8135
Email Address: sales@harrixwires.com Website: www.harrixwires.com